

PARTS LIST


ITEMS	DESCRIPTION	REF. DATA	REQ.
1	FOIL	CUPPER NICKEL ALLOY	1
2	GAGE LEAD	POLYURETHANE $\phi 0.14$	2
3	BASE	POLYIMIDE	1
4	COVER	POLYIMIDE	1
5	LEAD WIRE	7/0.12 2C DIA $\phi 1\text{mm}$ (WHITE)	1

SPECIFICATIONS

RESISTANCE	:	120.0 Ω \pm 1.0 Ω
GAGE LENGTH	:	0.3 mm
GAGE FACTOR	:	1.9~2.1
TEMPERATURE RANGE	:	-50 $^{\circ}\text{C}$ to 70 $^{\circ}\text{C}$



ミネベア株式会社
MINEBEA CO.,LTD.
計測機器事業部



単位 UNIT
mm
尺度 SCALE
FREE

材質 MATERIAL
-
表面粗さ SURF.ROUGH.
-
熱処理 HEAT TREAT.
-
表面処理 FINISH
-

作成日 DATE 2013/04/17
品名 DESCRIPTION
J-03-12T16W2MS

APPROVED	CHECKED	DRAWN
D. Inomori	E. MISAIZU	E. MISAIZU

一般公差 TOL	寸法 L	公差
	<L ≤ 4	±0.1
	4 < L ≤ 16	±0.2
	16 < L ≤ 63	±0.3
	63 < L ≤ 250	±0.5
	250 < L ≤ 1000	±0.8
	角度 DEG	±0.5

品番 PART NO. (MODEL NO.)
-
葉番 SHEET
/
図番 DRAWING NO.
G900472-1
改訂 REV.
-

符号 MARK	日付 DATE	変更事項 REASON	ECN NO.	担当 ENGINEER	承認 APPROVED
---------	---------	-------------	---------	-------------	-------------