





Rev.	Description	Initiator	Date
02	Updated model link.	PS	3/4/2006



NOTES:

1. MATERIAL: Stainless Steel
2. Sensing Reference frame origin at surface center of tool adapter.
3. Do not disassemble transducer. Doing so could damage transducer and void warranty.
4. For best accuracy, transducer must be mounted to surfaces rigid enough to support loads without deflection.
5. Cable must be connected to Transducer to maintain proper seal.
6. Cable is only IP68 rated at Transducer End. Transducer is IP68 rated in freshwater environment at a depth of up to 10 meters.



NOTES: UNLESS OTHERWISE SPECIFIED
 DO NOT SCALE DRAWING. DRAWN IN SOLIDWORKS.
 ALL DIMENSIONS ARE IN MILLIMETERS.



1031 Goodworth Drive, Apex, NC 27539, USA
 Tel: +1.919.772.0115 Email: info@ati-ia.com
 Fax: +1.919.772.8259 www.ati-ia.com
 ISO 9001 Registered Company

DRAWN BY: P.Sparrow, 2/16/06	TITLE IP68-10m DELTA Transducer		
CHECKED BY: D.Norton, 2/17/06	SCALE 1:1	SIZE B	DRAWING NUMBER 9230-05-1272-02
WEIGHT LBS: 5.8	PRODUCT RELEASE #	DATE:	SHEET 1 OF 1
ASSEMBLY REF:			

